


## Steel manifolds

# Model LTV Double Adjustable



### Features

- Primary or additional heat source
- Hydraulically adjustable
- A-rated pump
- Fill/drain lockshield valve
- Suitable for low-temperature systems
- Suitable for high-efficiency gas boilers
- Supplied with thermostatic valves 3/4" x eurocone
- Supplied with lockshields 3/4" x eurocone
- Ready for zone control, wired or wireless

### Number of loops

Article No.	Size	Article No.	Size	Article No.	Size	Article No.	Size
123461	1-port	123464	4-port	123467	7-port	123470	10-port
123462	2-port	123465	5-port	123468	8-port	123471	11-port
123463	3-port	123466	6-port	123469	9-port	123472	12-port

### Technical specifications

Medium:	water or water-glycol mixtures
Maximum percentage of glycol:	30%
Maximum working pressure:	4 bar
Maximum test pressure with cold water:	4 bar
Temperature setting range:	10 - 60 °C
Shut-down temperature safety thermostat:	55 °C
Thermometer scale:	0 - 60 °C
Primary connections of the manifold:	1 - 6 port: 1/2"   7 - 16 port: 3/4"
Connections of the underfloor heating pipes:	3/4" M - eurocone
Centre distance between the groups:	60 mm

### Dimensions (mm)

Size	Width	Height	Depth	Size	Width	Height	Depth
1-port	355	450	190	7-port	670	450	185
2-port	355	450	190	8-port	730	450	185
3-port	415	450	190	9-port	790	450	185
4-port	475	450	190	10-port	850	450	185
5-port	535	450	190	11-port	910	450	185
6-port	595	450	190	12-port	970	450	185

### Accessories

Article No.	Description
190055	Premium price mano-/thermometer (0 - 6 bar / 0 °C to 60 °C) assembled (I/O thermometer)
650019	Composite bend support 14 - 18 mm
650006	Composite bend support 20 - 22 mm
191840	Composite snap-on thermometer for underfloor heating pipe 16 mm
191842	Composite snap-on thermometer for underfloor heating pipe 20 mm
190020	Eurocone flow meter 240 l/h
191829	Automatic air vent 1/2" composite
650227	Composite spanner 27 mm for eurocone couplings