

Pipe

PE-Xc/ALU/PE-Xc + 6 mm insulation



Features

- Insulation colour: red or blue
- Insulation value (DIN 52613 / ISO 8497)
 - 0,040 W/mK at + 40 °C
 - 0,036 W/mK at + 10 °C
- KOMO certified (K42369/04)
- KIWA certified (K5166/11)
- Suitable for water (class 2 – 10 bar)
- Pipe keeps its shape after bending, this simplifies the installation
- Completely oxygen and diffusion-tight thanks to an integrated aluminum layer
- Suitable for transport of hot and cold drinking water (according to 98/83/EG)
- 10 years insurance for consequential damage up to 10 million euros per event per year

Diameter 16 x 2.0

Article No.	Description	Sales unit	Sales quantity
257410	PE-Xc/ALU/PE-Xc 16x2.0 / 100M + 6MM Insulation red	Per coil	1 coil
257411	PE-Xc/ALU/PE-Xc 16x2.0 / 100M + 6MM Insulation red - Pallet	Per pallet	13 coils
257412	PE-Xc/ALU/PE-Xc 16x2.0 / 100M + 6MM Insulation blue	Per coil	1 coil
257413	PE-Xc/ALU/PE-Xc 16x2.0 / 100M + 6MM Insulation blue - Pallet	Per pallet	13 coils

Diameter 20 x 2.0

Article No.	Description	Sales unit	Sales quantity
257420	PE-Xc/ALU/PE-Xc 20x2.0 / 50M + 6MM Insulation red	Per coil	1 coil
257421	PE-Xc/ALU/PE-Xc 20x2.0 / 50M + 6MM Insulation red - Pallet	Per pallet	14 coils
257422	PE-Xc/ALU/PE-Xc 20x2.0 / 50M + 6MM Insulation blue	Per coil	1 coil
257423	PE-Xc/ALU/PE-Xc 20x2.0 / 50M + 6MM Insulation blue - Pallet	Per pallet	14 coils

Diameter 26 x 3.0

Article No.	Description	Sales unit	Sales quantity
257430	PE-Xc/ALU/PE-Xc 26x3.0 / 25M + 6MM Insulation red	Per coil	1 coil
257431	PE-Xc/ALU/PE-Xc 26x3.0 / 25M + 6MM Insulation red - Pallet	Per pallet	12 coils
257432	PE-Xc/ALU/PE-Xc 26x3.0 / 25M + 6MM Insulation blue	Per coil	1 coil
257433	PE-Xc/ALU/PE-Xc 26x3.0 / 25M + 6MM Insulation blue - Pallet	Per pallet	12 coils